
UK Patent Application (19) GB (11) 2 072 957 A

- (21) Application No 8117259
- (22) Date of filing 5 Sep 1980
- (30) Priority data
- (31) 7905726
- (32) 6 Sep 1979
- (33) Brazil (BR)
- (43) Date of issue 7 Oct 1981
- (51) INT CL³
 (As given by ISA)
 F02B 75/02 F02D 39/02
- (52) Domestic classification H2C CG
- (56) Documents cited by ISA
 US, A, 3986351
 US, A, 4192265
 US, A, 3919986
 US, A, 4191150
- (58) Field of search by ISA US 123/48R, 78R, 315, 316
- (71) Applicant Urbano Ernesto Stumpf, Centro Tecnico Aeroespacial H-20-A, 106, 12200 São José Dos Campos-São Paulo, Brazil
- (72) Inventor Urbano Ernesto Stumpf
- (74) Agents
 Sanderson & Co., 97 High
 Street, Colchester, Essex,
 CO1 1TH

(54) Intake gas recirculation

(57) The present invention refers to the adapting of an internal combustion spark ignition engine to a multifuel engine having maximum thermodynamic efficiency possible with each particular fuel. The innovation consists in the variation of an effective compression ratio of the engine by recirculation of unburned gases from the cylinder to the intake tube (9) of the engine in a certain extent of the compression stroke of the engine. The recirculation of the intake gases is controlled by an

actuating device (5) with variable action. The basic effect of the invention is to confer to the engine the property of having a variable effective compression ratio optimized for a particular fuel and at the same time to use a large expansion ratio, being constant and independent of the compression ratio, in order to obtain a high thermodynamic efficiency and a low specific fuel consumption. The invention can be applied on existing engines or on new engines in order to get a highly efficient use of volatile or gaseous fuels, such as some petroleum derivates and its alternative fuels like the alcohols and biogases.



The state of the s

GB 2 072 957 A

UK Patent Application (19) GB (11) 2 072 957 A

- (21) Application No 8117259
- (22) Date of filing 5 Sep 1980
- (30) Priority data
- (31) 7905726
- (32) 6 Sep 1979
- (33) Brazil (BR)
- (43) Date of issue 7 Oct 1981
- (51) INT CL³
 (As given by ISA)
 F02B 75/02 F02D 39/02
- (52) Domestic classification H2C CG
- (56) Documents cited by ISA US, A, 3986351 US, A, 4192265 US, A, 3919986 US, A, 4191150
- (58) Field of search by ISA US 123/48R, 78R, 315, 316
- (71) Applicant
 Urbano Ernesto Stumpf,
 Centro Tecnico

(54) Intake gas recirculation

(57) The present invention refers to the adapting of an internal combustion spark ignition engine to a multifuel engine having maximum thermodynamic efficiency possible with each particular fuel. The innovation consists in the variation of an effective compression ratio of the engine by recirculation of unburned gases from the cylinder to the intake tube (9) of the engine in a certain extent of the compression stroke of the engine. The recirculation of the intake gases is controlled by an

actuating device (5) with variable action. The basic effect of the invention is to confer to the engine the property of having a variable effective compression ratio optimized for a particular fuel and at the same time to use a large expansion ratio, being constant and independent of the compression ratio, in order to obtain a high thermodynamic efficiency and a low specific fuel consumption. The invention can be applied on existing engines or on new engines in order to get a highly efficient use of volatile or gaseous fuels, such as some petroleum derivates and its alternative fuels like the alcohols and biogases.

ERRATUM

SPECIFICATION NO 2072957A

Front page heading (52) Domestic classification for H2C CG read FIB BIGIP

THE PATENT OFFICE 24 November 1981

Bas 86984/10

